

IX Special Precautions

Handling and Storage Requirements	Para. 1910.106 Fed. Register (OSHA), Vol. 37, No. 202, Part II; for storage - see NFPA, Section 6, Chapter 2. Flammable and combustible liquid fire and explosion prevention measures embrace one or more of the following techniques or principles, (a) exclusion of sources of ignition, (b) exclusion of air, (c) prevention of evaporation by keeping the liquids in closed containers or systems, (d) ventilation to prevent the accumulation of vapor within the flammable range, and (e) use of an atmosphere of inert gas instead of air
Precautionary Statements	Do not transfer to unmarked containers.

X Physical Properties

Boiling Point (°F)	Atmospheric Approximate 300-325 F	Melting Point (°F)		Solubility in water Negligible
Vapor Pressure (mm Hg & temp)	@ amb. temp. < 1	Specific Gravity (H ₂ O = 1)	@ 60 F/60 F, approx. 0.85	Appearance, Color, Odor, etc. Amber, transparent film on evaporation of solvent - mild odor.
Molecular Weight		Percent Volatile by Volume (%)	@ amb. temp. 58.5	Other
Vapor Density (air = 1)	Solvent in vapor form approx. 4.3	Evaporation Rate (EE = 1)	< 1	

Approved By: Robert B. Ohle

Date March 22, 1978

The above information is based on data available to us and is believed to be correct. However, NO WARRANTY of MERCHANTABILITY, FITNESS for any use or any other warranty is expressed or to be implied regarding the accuracy of these data, the results to be obtained from the use thereof, the hazards connected with the use of the material, or that any such use will not infringe any patent. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.